

### Model List for Pin Hole Lens

Model	Sensing Area	Focal Length	Back Focal Length	Flange Back Focal Length	F/#	TV Distortion	Field of View			Lens Construction	Length (mm)	TTL (mm)	Diameter X Thread	Usage
	(Inch)	(mm)	(mm)	(mm)		(%)	(degree)							
							Diagonal	Horizontal	Vertical					

**PIN HOLE LENS**

1. "I" letter on the model no. means to include the IR Cut-Off filter. 2. "A" letter on the model no. means the Cone barrel type. 3. "B" letter on the model no. means the Frat barrel type.  
 4. The length without the IR filter can be different with the length included the IR filter. Please absolutely check up the specification.

V44073PIA	1/4"	4.46	3.83	2.45	2.5	-4.9	61.3	47.9	35.4	1A/3G/IRF	8.09	10.54	M12X0.5P	CCD
	1/3"					-8.9	88.1	66.1	47.9					
V44073PA	1/4"	4.46	3.57	2.99	2.5	-4.9	61.3	47.9	35.4	1A/3G	7.29	10.28	M12X0.5P	CCD
	1/3"					-8.9	88.1	66.1	47.9					
V44073PIB	1/4"	4.46	3.83	2.45	2.5	-4.9	61.3	47.9	35.4	1A/3G/IRF	8.09	10.54	M12X0.5P	CCD
	1/3"					-8.9	88.1	66.1	47.9					
V38090PB	1/4"	3.80	3.29	2.85	2.5	-8	68.0	52.5	38.5	1A/3G	7.40	10.25	M12X0.5P	CCD
	1/3"					-22.7	103.08	73.7	52.54					
V38090PIA	1/4"	3.80	3.53	2.27	2.5	-8	68.0	52.5	38.5	1A/3G/IRF	8.1	10.37	M12X0.5P	CCD
	1/3"					-22.7	103.08	73.7	52.54					
V34094PIB	1/4"	3.43	3.62	2.57	2.5	-10.38	96.1	68	47.9	1A/3G/IRF	8.22	10.79	M12X0.5P	CCD
V44094PIB	1/4"	4.44	4.03	2.61	2.5	-4.65	62.8	48.8	35.8	1A/3G/IRF	8.46	11.07	M12X0.5P	CCD
	1/3"					-9.51	94	68	48.8					
V33120PIB	1/4"	3.30	3.31	2.76	2.5	-6.44	83.4	65.0	47.9	1 A/4G/IRF	8.87	11.63	M12X0.5P	CCD
	1/3"					-13.01	121.8	90.0	65.0					